



180 Lake Ave North
Paynesville, MN 56362
Phone: 1-800-864-1649
www.master-mfg.com



MASTER
MANUFACTURING

THREADED MANIFOLD TO QA PUMP

Note: Do not return product to the distributor/dealer for warranty work. Call (800) 864-1649 for any warranty work or replacement parts.

INTRODUCTION

The purpose of this manual is to assist you in the assembly, operation and maintenance of your sprayer or accessories. Please read through this manual completely too fully understand how to operate and maintain your equipment. This product has been manufactured to provide years of dependable service; proper operation and maintenance will ensure its dependability. Keep your manual in a safe, convenient place for future reference. Always mention the model and part number in any correspondence.

ASSEMBLY

Tools Needed:

- 15/16" Wrench or Crescent Wrench
- Thread Sealant

Frame Assembly

- 1.) Obtain the Manifold Assembly and remove the 3/8" MPT Fitting from the Manifold.
- 2.) Obtain the 1/2" NPT to QA Fitting and apply thread sealant to the threads
- 3.) Thread onto Manifold Assembly in the port you just removed the 3/8" MPT Fitting from. Make sure the fitting is threaded on TIGHT in order to prevent leaking.
- 4.) Obtain QA Pump and Slide Locking clip on outlet port to the open position.
- 5.) Slide Manifold Assembly into QA Pump outlet port.



